

PNEUMATISK FLAKLÅSCYLINDER

C63MP2C-XX

Produktgrupp 0519



| Artikelnummer | Temperatur | Diameter mm | Längd |
|-------------------|------------|-------------|-------|
| C63MP2C080A0100GS | -20°C | Ø80 | 100 |
| C63MP2C080A0125GS | -20°C | Ø80 | 125 |
| C63MP2C080A0160GS | -20°C | Ø80 | 160 |
| C63MP2C080A0200GS | -20°C | Ø80 | 200 |
| C63MP2C080A0250GS | -20°C | Ø80 | 250 |
| C63MP2C080A0320GS | -20°C | Ø80 | 320 |
| C63MP2C100A0100GS | -20°C | Ø100 | 100 |
| C63MP2C100A0125GS | -20°C | Ø100 | 125 |
| C63MP2C100A0160GS | -20°C | Ø100 | 160 |
| C63MP2C100A0200GS | -20°C | Ø100 | 200 |
| C63MP2C100A0250GS | -20°C | Ø100 | 250 |
| C63MP2C100A0320GS | -20°C | Ø100 | 320 |
| C63MP2C080A0100ZS | -40°C | Ø80 | 100 |
| C63MP2C080A0160ZS | -40°C | Ø80 | 160 |
| C63MP2C080A0200ZS | -40°C | Ø80 | 200 |
| C63MP2C080A0250ZS | -40°C | Ø80 | 250 |
| C63MP2C080A0320ZS | -40°C | Ø80 | 320 |
| C63MP2C100A0100ZS | -40°C | Ø100 | 100 |
| C63MP2C100A0160ZS | -40°C | Ø100 | 160 |
| C63MP2C100A0200ZS | -40°C | Ø100 | 200 |
| C63MP2C100A0250ZS | -40°C | Ø100 | 250 |
| C63MP2C100A0320ZS | -40°C | Ø100 | 320 |