

# Hydroscand T1112, twin



<b>Product group</b>	110
<b>Color</b>	Black
<b>Safety factor</b>	1:4
<b>Bundled pipes/hoses</b>	2
<b>Cover tube resistance</b>	Abrasion, Oil, Weather
<b>Cover tube material</b>	PU
<b>Max temperature (°C)</b>	100
<b>Reinforcement layers</b>	1
<b>Reinforcement materials</b>	Steel wire
<b>Min temperature (°C)</b>	-40

The hose is well suitable for high pressure hydraulics. The hose is also suited for high pressure gas applications, but then needs to be pin-pricked.;Due to the inner tube of polyester, the hose will retain its flexibility in cold temperatures. NOTE! Air and water max +70°C

Part no	Working pressure (MPa)	Bend radius (mm)	ID (inch)	ID (mm)	OD (mm)	Weight (kg)
10320303	36	30	3/16"	5	9.7	0.24
10320404	31	40	1/4"	6.5	11.7	0.3
10320505	25	55	5/16"	8	13.2	0.38
10320606	22.5	65	3/8"	10	16.5	0.44
10320808	19	85	1/2"	13	18.8	0.58
10321010	14	115	5/8"	16	22	0.67
10321212	11.5	145	3/4"	19	25.8	0.89
10321616	9.5	180	1"	25	33	1.24

