

# HYDROSCAND SUPERTWIN T7012, TWIN



<b>Product group</b>	110
<b>Color</b>	Black
<b>Cover design</b>	Pin-pricked
<b>Media description</b>	Oil
<b>Safety factor</b>	1:4
<b>Bundled pipes/hoses</b>	2
<b>Cover tube resistance</b>	Abrasion, Oil
<b>Cover tube material</b>	PU
<b>Max temperature (°C)</b>	100
<b>Reinforcement layers</b>	1
<b>Reinforcement materials</b>	Polyester
<b>Min temperature (°C)</b>	-40

The hose is well suitable for high pressure hydraulics and high pressure gas applications. Due to the inner tube of polyester, the hose will retain its flexibility in cold temperatures. Equivalent to SAE 100 R8 regarding pressure and SAE 100 R7 regarding dimensions.  
NOTE! Air and water max +70°C

Part no	ID (inch)	ID (mm)	OD (mm)	Working pressure (MPa)	Bend radius (mm)	Weight (kg)
<b>10470303</b>	3/16"	5	9.6	21	25	0.12
<b>10470404</b>	1/4"	6.5	12.2	21	35	0.19
<b>10470505</b>	5/16"	8	14.3	19	45	0.25
<b>10470606</b>	3/8"	10	16	16	55	0.29
<b>10470808</b>	1/2"	13	20.3	14	75	0.43

