

HYDROSCAND T6071



| | |
|--------------------------------|-------------|
| Product group | 110 |
| Color | Black |
| Cover design | Pin-pricked |
| Safety factor | 1:4 |
| Bundled pipes/hoses | 1 |
| Inner tube material | PE |
| Cover tube material | PE |
| Max temperature (°C) | 100 |
| Reinforcement layers | 1 or 2 |
| Reinforcement materials | Polyester |
| Min temperature (°C) | -55 |

This hose is suited for hydraulics with very high pressures, e.g. high pressure pumps and heavy duty applications. Due to the inner tube of polyester, the hose will retain its flexibility in cold temperatures. NOTE! Water max +70°C.

| Part no | ID (mm) | OD (mm) | Working pressure (MPa) | Bend radius (mm) | ID (inch) | Weight (kg) |
|----------|---------|---------|------------------------|------------------|-----------|-------------|
| 10570103 | 5 | 9.6 | 21 | 25 | 3/16" | 0.06 |
| 10570104 | 6.5 | 12.2 | 21 | 35 | 1/4" | 0.1 |
| 10570105 | 8 | 14.3 | 21 | 45 | 5/16" | 0.13 |
| 10570106 | 10 | 16.6 | 21 | 45 | 3/8" | 0.17 |
| 10570108 | 13 | 22.5 | 21 | 70 | 1/2" | 0.3 |
| 10570110 | 16 | 26.1 | 21 | 100 | 5/8" | 0.1 |

