

EGEFLEX 2



Product group	100
Color	Black
Cover design	Wrapped
Safety factor	1:4
Bundled pipes/hoses	1
Cover tube resistance	Oil, Weather
Inner tube resistance	Oil
Media description	Oil
Cover tube material	Synthetic rubber
Inner tube material	Synthetic rubber
Max temperature (°C)	100
Reinforcement layers	2
Reinforcement materials	Steel wire
Min temperature (°C)	-40

A hose for applications with medium to high pressures and a lot of external abrasion. Equivalent to EN 853 2SN. Approved by MSHA (flame resistant). The certificates refer to dimensions 3/1"- 1". Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/bobbin and a minimum length of 5 meters per length.

Part no	OD (mm)	Working pressure (MPa)	Bend radius (mm)	ID (inch)	ID (mm)	Weight (kg)
11020003	13.4	41.5	90	3/16"	5	0.3
11020004	15	40	100	1/4"	6.5	0.38
11020005	16.6	35	115	5/16"	8	0.44
11020006	19	33	130	3/8"	9.5	0.55
11020008	22.2	27.5	180	1/2"	13	0.69
11020010	25.4	25	200	5/8"	16	0.76
11020012	29.3	21.5	240	3/4"	19	0.91
11020016	38.1	16.5	300	1"	25	1.32
11020020	48.3	12.5	420	1 1/4"	32	1.98
11020024	54.6	9	500	1 1/2"	38	2.37
11020032	67	7.8	630	2"	51	2.82
11020040	73.3	6.9	762	2 1/2"	63	3.84
11020048	91.3	5	900	3"	76.2	4.04

