

Kappaflex 2 CO Smooth



Product group	100
Color	Green
Cover design	Smooth
Inner tube resistance	Oil
Media description	Oil
Safety factor	1:4
Bundled pipes/hoses	1
Cover tube resistance	Abrasion, Oil, Ozone
Inner tube material	Synthetic rubber
Cover tube material	Synthetic rubber
Hose label	orange
Max temperature (°C)	100
Reinforcement layers	2
Reinforcement materials	Steel wire
Min temperature (°C)	-40

Ozone resistant hose for applications with high pressures, well suited for marine applications. Exceeds EN 857 2SC. DNV-, MED- and MSHA-approved. Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/bobbin and a minimum length of 5 meters.

Part no	ID (mm)	OD (mm)	Working pressure (MPa)	Bend radius (mm)	ID (inch)	Weight (kg)
11041704	6.5	13.4	42.5	75	1/4"	0.29
1104170430	6.5	13.4	42.5	75	1/4"	0.29
11041705	8	15	40	85	5/16"	0.34
11041706	10	17.2	35	90	3/8"	0.42
1104170630	10	17.2	35	90	3/8"	0.42
11041708	13	20.4	31	130	1/2"	0.58
1104170830	13	20.4	31	130	1/2"	0.58
11041710	16	23.9	28	160	5/8"	0.7
11041712	19	27.7	28	195	3/4"	0.83
1104171230	19	27.7	28	195	3/4"	0.82
11041716	25	35.4	21	250	1"	1.19

