Kappaflex 2K CO Rock



Product group	100
Color	Black
Cover design	Wrapped
Safety factor	1:4
Bundled pipes/hoses	1
Cover tube resistance	Abrasion, Oil, Weather
Inner tube resistance	Oil
Media description	Oil
Cover tube material	Synthetic rubber
Hose label	Grön med svart text
Inner tube material	Synthetic rubber
Certificate	Det Norske Veritas, MED, MSHA
Max temperature (°C)	100
Reinforcement layers	2
Reinforcement materials	Steel wire
Min temperature (°C)	-50

This hose is suitable for applications with very high pressures (47.0-32.7 MPa). Exceeds EN 857 2SC (40.0 - 16.5 MPa).

Part no	OD (mm)	Working pressure (MPa)	Bend radius (mm)	ID (inch)	ID (mm)	Weight (kg)
11056304	13.4	45	45	1/4"	6.5	0.27
1105630430	13.4	45	45	1/4"	6.5	0.27
11056305	15	42	60	5/16"	8	0.32
1105630530	15	42	60	5/16"	8	0.32
11056306	17.4	38.5	70	3/8"	10	0.38
1105630630	17.4	38.5	70	3/8"	10	0.38
11056308	20.6	34.5	90	1/2"	13	0.53
1105630830	20.6	34.5	90	1/2"	13	0.53
11056310	23.6	29	130	5/8"	16	0.66
11056312	27.7	28	160	3/4"	19	0.87
1105631230	27.7	28	160	3/4"	19	0.85
11056316	35.6	20	210	1"	25	1.17
11056320	43.5	17.5	300	1 1/4"	32	1.59

