

# Deltaflex 4 CT



|                                |                               |
|--------------------------------|-------------------------------|
| <b>Product group</b>           | 110                           |
| <b>Color</b>                   | Black                         |
| <b>Cover design</b>            | Wrapped                       |
| <b>Bundled pipes/hoses</b>     | 1                             |
| <b>Cover tube resistance</b>   | Abrasion, Heat, Weather,      |
| <b>Inner tube resistance</b>   | Oil                           |
| <b>Safety factor</b>           | 1:4                           |
| <b>Hose label</b>              | yellow                        |
| <b>Certificate</b>             | Det Norske Veritas, MED, MSHA |
| <b>Max temperature (°C)</b>    | 121                           |
| <b>Reinforcement layers</b>    | 4                             |
| <b>Reinforcement materials</b> | Steel wire                    |
| <b>Min temperature (°C)</b>    | -40                           |

Flexible hydraulic hose for high pressures in combination with high pulsations. The external polymer rubber has low friction and extra abrasion resistance. Working pressure is equivalent to, or exceeds, EN 856 4SP

| Part no  | Working pressure (MPa) | Bend radius (mm) | ID (inch) | ID (mm) | OD (mm) | Weight (kg) |
|----------|------------------------|------------------|-----------|---------|---------|-------------|
| 11151006 | 44.5                   | 130              | 3/8"      | 10      | 21.4    | 0.7         |
| 11151008 | 42.5                   | 180              | 1/2"      | 13      | 24.6    | 0.85        |
| 11151010 | 39                     | 225              | 5/8"      | 16      | 28.2    | 1.11        |
| 11151012 | 35                     | 280              | 3/4"      | 19      | 32.2    | 1.41        |
| 11151016 | 32                     | 340              | 1"        | 25      | 39.7    | 1.86        |
| 11151020 | 34.5                   | 460              | 1 1/4"    | 32      | 45.5    | 2.57        |
| 11151024 | 29                     | 560              | 1 1/2"    | 38      | 53.5    | 3.32        |
| 11151032 | 25                     | 700              | 2"        | 51      | 68.1    | 4.7         |

