

Isobar 35 CO



| | |
|--------------------------------|--------------------------|
| Product group | 120 |
| Color | Black |
| Cover design | Wrapped |
| Bundled pipes/hoses | 1 |
| Cover tube resistance | Abrasion, Heat, Weather, |
| Inner tube resistance | Oil |
| Safety factor | 1:4 |
| Cover tube material | Synthetic rubber |
| Hose label | white |
| Inner tube material | Rubber |
| Certificate | MSHA |
| Max temperature (°C) | 121 |
| Reinforcement layers | 4 |
| Reinforcement materials | Steel wire |
| Min temperature (°C) | -40 |

The hose is suitable for very high pressures in combination with very high impulses. High flexibility and a lot of external abrasion. MSHA-approved (flame resistant). Ferrule: 4200-19-xx (use only with 3/8" - 1") 4200-20-20 (use only with 1 1/4") 4400-09-xx (interlock) 4700-09-xx (use only with 3/4" - 1 1/4")

| Part no | Working pressure (MPa) | Bend radius (mm) | ID (inch) | ID (mm) | OD (mm) | Weight (kg) |
|----------|------------------------|------------------|-----------|---------|---------|-------------|
| 11351332 | 35 | 630 | 2" | 51 | 71.6 | 6.26 |

