

# IsoBar CO Rock



<b>Product group</b>	110
<b>Color</b>	Black
<b>Cover design</b>	Wrapped
<b>Inner tube resistance</b>	Oil
<b>Safety factor</b>	1:4
<b>Bundled pipes/hoses</b>	1
<b>Cover tube resistance</b>	Abrasion, Oil, Weather
<b>Hose label</b>	Orange and white text
<b>Certificate</b>	MSHA
<b>Max temperature (°C)</b>	120
<b>Reinforcement layers</b>	4
<b>Reinforcement materials</b>	Steel wire
<b>Min temperature (°C)</b>	-40

Flexible hydraulic hose, suitable for very high pressures in combination with very high impulses and a lot of external abrasion. The working pressure is equivalent to, or exceeds, SAE-100 R15. Ferrule: 4400-09-xx (use only with 3/4" and 1") 4400-14-xx (use only with 1 1/4 1 1/2") 4700-09-xx use only with 3/4" and 1") 4700-10-xx use only with 1 1/4" and 1 1/2")

Part no	ID (inch)	ID (mm)	OD (mm)	Working pressure (MPa)	Bend radius (mm)	Weight (kg)
11358408	1/2"	13	22.9	35	90	0.74
11358412	3/4"	19	30.3	35	141	1.2
11358416	1"	25	38.1	35	153	1.94
11358420	1 1/4"	32	49.7	35	210	3.87

