

# INDUSTRIAL COOLING HOSE, FIBERGLASS



<b>Product group</b>	140
<b>Color</b>	White
<b>Safety factor</b>	1:3
<b>Bundled pipes/hoses</b>	1
<b>Media description</b>	Water
<b>Antistatic wire</b>	No
<b>Cover tube material</b>	EPDM
<b>Flat coil</b>	No
<b>Inner tube material</b>	EPDM
<b>Max temperature (°C)</b>	120
<b>Reinforcement layers</b>	No extra reinforcement
<b>Reinforcement materials</b>	Textile
<b>Min temperature (°C)</b>	-30

Used as a protection and cooling hose where the working temperature is high, e.g. melting furnaces and foundries. The cover cord is made of fiberglass, which gives the hose a good resistance towards flames. Sustains 530° C temporary radiation as well as glowing steel spatter.

Part no	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Length meter per coil	OD (mm)	Weight (kg)
14020008	50	1.2	13	40	29	0.44
14020010	85	1.2	16	40	32	0.77
14020012	95	1.2	19	40	35	0.69
14020016	125	1.2	25	40	41	0.73
14020020	160	1.2	32	40	48	0.88
14020024	380	1.2	38	40	55	1.1
14020026	400	1.2	40	40	57	1.9
14020030	450	1.2	45	40	63	2.1
14020032	250	1.2	51	40	71	2.24
14020040	630	1.2	63.5	40	81	2.91
14020048	380	1.2	76	40	96	3.3