SPIRAL SUCTION HOSE, SUPER ELASTIC PVC



Product group	140
Color	Grey
Cover design	Corrugated
Safety factor	1:3
Bundled pipes/hoses	1
Media description	Water
Antistatic wire	No
Cover tube material	PVC
Flat coil	No
Max temperature (°C)	55
Reinforcement layers	No extra reinforcement
Reinforcement materials	PVC
Min temperature (°C)	-25

A suction hose for sewage trucks, grains and fertilizing. Pliable and flexible at low temperatures. The extra hard PVC spiral gives an extraordinary protection against external abrasion.

Part no	Bend radius (mm)	Working pressure (MPa)	Vacuum pr. Max%	ID (mm)	Length meter per coil	OD (mm)	Weight (kg)
14071016	100	0.7	90	25	50	33.8	0.48
14071020	130	0.6	90	32	50	40.8	0.6
14071024	150	0.6	90	38	50	46.8	0.7
14071032	200	0.5	90	50	50	61	1.05
14071040	250	0.45	90	63	50	74	1.39
14071048	300	0.4	90	76	30	89	1.7
14071056	360	0.35	90	89	30	102.4	2.25
14071064	400	0.35	90	102	30	116.6	2.7
14071069	440	0.35	90	110	20	125	3.1
14071080	510	0.25	90	127	20	143.6	3.9
14071096	610	0.2	90	152	20	170	5



HYDROSCAND