## Universal PU hose, 20 Bar

	Product group	140	
a.	Cover design	Smooth	
Š.	Color	Green	
	<b>Bundled pipes/hoses</b>	1	
	Media description	Air pressu	re
	Safety factor	1:3	
	Cover tube material	PVC/NBR	
	Flat coil	No	
	Inner tube material	PVC	
	Antistatic wire	No	
	Max temperature (°C)	60	
	Reinforcement layers	No extra r <mark>e</mark>	
	Reinforcement materials	Textile	
	Min temperature (°C)	-15	

Smooth Green 1 Air pressure, Air 1:3 PVC/NBR No PVC No 60 No extra reinforcement Textile -15

A very light hose, only 2/3 of a conventional PVC or rubber hose. It is very flexible and has a high ozone resistance. It is also resistant towards lubricates, oils and non-aggressive chemicals. Well suited for pneumatic tools and sandblasting. Food quality.

Part no	Working pressure (MPa)	ID (mm)	Length meter per coil	OD (mm)	Bend radius (mm)	Weight (kg)
14243004	2	6	100	10	20	0.07
14243005	2	8	60	12	22	0.11
14243006	2	10	50	15	38	0.13
14243008	2	13	30	19	55	0.2
14243010	2	16	25	23	60	0.25



