

Yachtoil SW, marine fuel hose, ISO 7840



Product group	140
Color	Black
Cover design	Smooth
Bundled pipes/hoses	1
Cover tube resistance	Flame resistant, Oil, Weather
Media description	Oil and gasoline
Antistatic wire	No
Cover tube material	CR
Flat coil	No
Inner tube material	NBR
Certificate	CE, RINA
Max temperature (°C)	80
Reinforcement layers	1
Reinforcement materials	Textile
Min temperature (°C)	-35

A very flexible fuel hose that is resistant to gasoline, unleaded gasoline and diesel. The hose is manufactured according to SS-EN ISO 7840 A1 regarding flame resistance and permeability. This means that it can sustain 2,5 minutes in open fire without leaking. For larger dimensions, see 1432-31. ISO 7840 A1 E10/B10 compatible.

Part no	Bend radius (mm)	Burst pressure (MPa)	Working pressure (MPa)	ID (mm)	Length meter per coil	OD (mm)	Weight (kg)
14323002	25	3	1	4	50	14.5	0.23
14323003	50	3	1	5	50	12.5	0.15
14323004	60	3	1	6	50	13.5	0.17
14323005	80	3	1	8	50	16.5	0.24
14323006	100	3	1	10	50	18.5	0.28
14323008	130	3	1	13	50	22.5	0.4
14323010	160	3	1	16	50	25.5	0.46
14323012	190	3	1	19	50	29.5	0.6
14323016	250	3	1	25	50	35.8	0.75

