

Yachtoil SW, marine fuel hose, ISO 7840



Product group	140
Color	Black
Cover design	Wrapped
Media description	Oil and gasoline
Safety factor	1:3
Bundled pipes/hoses	1
Cover tube resistance	Flame resistant, Oil, Weather
Inner tube material	NBR
Antistatic wire	No
Cover tube material	CR
Flat coil	No
Certificate	CE, RINA
Max temperature (°C)	80
Reinforcement layers	2
Reinforcement materials	Textile
Min temperature (°C)	-20

This hose is manufactured according to SS-EN ISO 7840 A1 regarding flame resistance and permeability. This means that it can sustain 2,5 minutes in open fire without leaking. It is used as a fuel refill hose on smaller boats. ISO 7840 A1 E10/B10 compatible.

Part no	Length meter per coil	OD (mm)	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Weight (kg)
14323112	40	32	120	0.25	19	0.64
14323116	40	38	150	0.25	25	0.74
14323120	61	41	160	0.5	32	0.84
14323124	61	50	190	0.5	38	1.24
14323126	40	53	240	0.25	40	1.44
14323132	61	63	250	0.5	51	1.58
14323138	61	67	305	0.5	55	-
14323140	61	76	320	0.5	63	2.34
14323148	20	88	760	0.25	76	2.1

