

RAGOIL, FUEL HOSE



Product group	140
Cover design	Wrapped
Inner tube resistance	Oil
Media description	Oil and gasoline
Safety factor	1:2.5
Bundled pipes/hoses	1
Cover tube resistance	Oil
Flat coil	No
Inner tube material	Synthetic rubber
Antistatic wire	No
Cover tube material	Synthetic rubber
Max temperature (°C)	80
Reinforcement materials	Stainless steel wire
Min temperature (°C)	-40

The hose is designed for oil and diesel pipes, and also to be used as a lubrication oil hose. It does not sustain E85 and RME. For fuel fittings, see chapter 5:0

Part no	ID (mm)	Length meter per coil	OD (mm)	Bend radius (mm)	Working pressure (MPa)	Weight (kg)
14370002	3.5	20	8.5	25	3.2	0.13
14370003	4.5	20	9.5	25	3	0.15
14370004	5.5	20	10.5	25	3	0.19
14370006	7.5	20	12.5	30	2.4	0.22
14370008	9.5	20	15	40	2	0.25
14370010	11	20	17.5	45	2	0.29
14370013	14	20	21.5	50	1.8	0.37
14370016	17.5	20	26	70	1.4	0.48
14370020	20.5	20	32	90	1.4	0.55

