

Cobra chemical hose EPDM EN12115



Product group	140
Color	Black
Cover design	Wrapped
Safety factor	1:4
Bundled pipes/hoses	1
Media description	Chemicals
Antistatic wire	No
Cover tube material	EPDM
Flat coil	No
Inner tube material	EPDM
Max temperature (°C)	120
Reinforcement layers	2
Reinforcement materials	Steel wire, Textile
Min temperature (°C)	-40

Suction and pressure hose for aggressive chemicals. used for loading and unloading of gas trucks, railroad cars, cargo liners and in stationary installations in chemical premises. The hose is flexible and resists external abrasion well. Electrical resistance < 106 Ohm. According to EN 12115 TRbF131/2.

Part no	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	OD (mm)	Weight (kg)
14501012	65	1.6	19	90	40	31	1.5
14501016	90	1.6	25	90	40	37	0.81
14501020	120	1.6	32	90	40	44	0.99
14501024	155	1.6	38	90	40	51	1.3
14501032	215	1.6	50	90	40	66	2.13
14501040	275	1.6	63.5	90	40	79.5	2.86
14501048	330	1.6	75	90	40	91	3.41
14501064	450	1.6	100	90	40	116	4.41

