

Vacuum hose, Polyurethane



Product group	140
Color	Transparent
Cover design	Corrugated
Bundled pipes/hoses	1
Media description	Food and beverage, Materials, Ventilation
Antistatic wire	No
Cover tube material	PU
Flat coil	No
Inner tube material	PU
Max temperature (°C)	85
Reinforcement layers	No extra reinforcement
Reinforcement materials	PVC
Min temperature (°C)	-25

A hose suitable for ventilation; suction of gases, smoke, dust pellets; and for transportation of mineral wool insulation. The hose is internally smooth and very flexible. Also available in antistatic design, see 1463-40-xx. Food approved.

Part no	OD (mm)	Bend radius (mm)	Working pressure (MPa)	Vacuum pr. Max%	ID (mm)	Length meter per coil	Weight (kg)
14631020	33.2	32	0.06	40	32	20	0.19
14631024	39.2	38	0.04	30	38	20	0.25
14631030	46.2	45	0.04	30	45	20	0.32
14631032	51.4	50	0.04	30	50	20	0.39
14631039	61.4	60	0.04	30	60	20	0.44
14631040	64.4	65	0.03	30	63	20	0.47
14631048	76.4	75	0.03	30	75	20	0.6
14631050	81.4	80	0.02	30	80	20	0.65
14631055	91.6	90	0.02	30	90	20	0.75
14631064	101.6	100	0.02	30	100	20	0.85
14631080	126.6	125	0.02	30	125	20	1.17
14631096	153.8	150	0.01	30	152	20	1.45
14631160	161.8	160	0.01	30	160	20	1.7

