Granulite, transportation hose M52, antistatic wire



Product group	140
Color	Black
Cover design	Wrapped
Inner tube resistance	Abrasion
Media description	Materials
Safety factor	1:3
Bundled pipes/hoses	1
Cover tube resistance	Abrasion, Ozone, Weather
Flat coil	No
Inner tube material	NR/SBR
Antistatic wire	No
Cover tube material	SBR
Max temperature (°C)	90
Reinforcement layers	2
Reinforcement materials	Steel wire, Textile
Min temperature (°C)	-40

Transportation hose for sanitation vehicles. Can also be used as the bent part in central vacuum applications. Antistatic wire

Part no	ID (mm)	Vacuum pr. Max%	Length meter per coil	OD (mm)	Bend radius (mm)	Working pressure (MPa)	Weight (kg)
14675203	204	90	10	222	820	0.3	10
14675232	51	90	40	64	210	0.5	1.7
14675240	63	90	40	76	250	0.5	2
14675248	76	90	40	90	300	0.5	2.7
14675256	90	90	40	104	350	0.5	3.2
14675264	102	90	40	117	400	0.5	3.6
14675269	110	90	40	124	430	0.5	3.9
14675274	115	90	40	131	450	0.5	4.3
14675280	127	90	20	143	510	0.3	5
14675285	140	90	20	156	580	0.3	6.2
14675296	152	90	20	168	640	0.3	5.7



HYDROSCAND