

# GAS TRUCK HOSE EN12115, 16 BAR ANTISTATIC WIRE



<b>Product group</b>	140
<b>Color</b>	Black
<b>Cover design</b>	Wrapped
<b>Media description</b>	Oil and gasoline
<b>Safety factor</b>	1:4
<b>Bundled pipes/hoses</b>	1
<b>Flat coil</b>	No
<b>Inner tube material</b>	NBR
<b>Antistatic wire</b>	No
<b>Cover tube material</b>	CR
<b>Max temperature (°C)</b>	80
<b>Reinforcement layers</b>	2
<b>Reinforcement materials</b>	Steel wire, Textile
<b>Min temperature (°C)</b>	-30

Gas truck hose fulfilling the requirements according to EN12115. The hose is designed to be used with petroleum products with no more than 55% aromatic contents. Designed with textile reinforcement with a twin spiral and two antistatic wires. Electric resistance: <106 Ohm. Vacuum = 90%. Oil, weather and abrasion resistant cover.

Part no	ID (mm)	Vacuum pr. Max%	Length meter per coil	OD (mm)	Bend radius (mm)	Working pressure (MPa)	Weight (kg)
14692016	25	90	40	37	150	1.6	0.8
14692020	32	90	40	44	175	1.6	0.98
14692024	38	90	40	51	225	1.6	1.14
14692032	51	90	40	67	275	1.6	1.69
14692040	63.5	90	40	80	300	1.6	2.55
14692048	76	80	40	92	350	1.6	2.83
14692064	102	80	40	118	450	1.6	3.95

