HYDROSCAND ARCTIC PVC SUCTION HOSE -40°C



Product group	140
Cover design	Corrugated
Bundled pipes/hoses	1
Media description	Water
Safety factor	1:3
Cover tube material	PVC
Flat coil	No
Inner tube material	PVC
Antistatic wire	No
Max temperature (°C)	45
Reinforcement layers	1
Reinforcement materials	PVC
Min temperature (°C)	-40

A suction hose for sewage trucks, grains and fertilizing. Extremely pliable and flexible at very low temperatures. The extra hard PVC spiral provides excellent protection against external abrasion/friction. The hose is oil resistant.

Part no	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	OD (mm)	Bend radius (mm)	Weight (kg)
15081032	0.3	51	90	30	62	165	1.1
1508103290	0.3	51	90	50	62	165	1.1
15081048	0.3	76	90	30	89	260	1.8
1508104890	0.3	76	90	50	89	260	1.8
15081056	0.25	89	90	30	103	300	2.25
15081064	0.2	102	90	30	117	330	2.8
1508106490	0.3	102	90	50	117	350	2.8
15081080	0.1	127	90	20	144	420	4
15081096	0.1	152	90	20	170	510	5

