
Blue silicon hose90° 150x150 mm



Product group	140
Safety factor	1:3
Bundled pipes/hoses	1
Media description	Water
Antistatic wire	No
Cover tube material	Silicon
Flat coil	No
Inner tube material	Silicon
Max temperature (°C)	180
Min temperature (°C)	-50

Excellent hose for cooling and heating systems in buses and trucks. The silicone withstands contact with oil, but must NOT be used for oil transportation nor oil bath. Other dimensions are available on request.

Part no	Working pressure (MPa)	ID (mm)	OD (mm)	Reinforcement layers	Reinforcement materials	Weight (kg)
15099008	0.79	12	21	No extra reinforcement	Clean	0.08
15099010	0.75	16	25	No extra reinforcement	Clean	0.1
15099012	0.66	19	28	No extra reinforcement	Clean	0.12
15099014	0.61	22	31	No extra reinforcement	Clean	0.14
15099016	0.58	25	34	No extra reinforcement	Clean	0.16
15099018	0.57	28	37	No extra reinforcement	Clean	0.18
15099020	0.53	32	41	No extra reinforcement	Clean	0.2
15099022	0.51	35	43	No extra reinforcement	Clean	0.22
15099024	0.5	38	47	No extra reinforcement	Clean	0.24
15099025	0.48	40	49	No extra reinforcement	Clean	0.25
15099026	0.47	42	51	No extra reinforcement	Clean	0.27
15099030	0.45	45	54	No extra reinforcement	Clean	0.29
15099032	0.37	51	61	No extra reinforcement	Clean	0.32
15099037	0.29	57	65	No extra reinforcement	Clean	0.36
15099038	0.31	55	65	No extra reinforcement	Clean	0.35
15099039	0.27	60	70	No extra reinforcement	Clean	0.38
15099040	0.23	65	75	No extra reinforcement	Clean	0.41
15099044	0.22	70	80	No extra reinforcement	Clean	0.44
15099048	0.2	76	86	No extra reinforcement	Clean	0.48



HYDROSCAND

Part no	Working pressure (MPa)	ID (mm)	OD (mm)	Reinforcement layers	Reinforcement materials	Weight (kg)
15099053	0.17	85	95	No extra reinforcement	Clean	0.54
15099056	0.15	89	100	No extra reinforcement	Clean	0.56
15099064	0.13	102	113	No extra reinforcement	Clean	0.65

