

# AIRCOMP COMPRESSOR HOSE

## 180°C



|                                |                        |
|--------------------------------|------------------------|
| <b>Product group</b>           | 140                    |
| <b>Color</b>                   | Blue                   |
| <b>Cover design</b>            | Wrapped                |
| <b>Safety factor</b>           | 1:3                    |
| <b>Bundled pipes/hoses</b>     | 1                      |
| <b>Inner tube resistance</b>   | Heat                   |
| <b>Media description</b>       | Air pressure, Air      |
| <b>Antistatic wire</b>         | No                     |
| <b>Cover tube material</b>     | EPDM                   |
| <b>Flat coil</b>               | No                     |
| <b>Inner tube material</b>     | EPR                    |
| <b>Max temperature (°C)</b>    | 180                    |
| <b>Reinforcement layers</b>    | No extra reinforcement |
| <b>Reinforcement materials</b> | Steel wire, Textile    |
| <b>Min temperature (°C)</b>    | -40                    |

A hose for air connections from compressors on trucks for bulk transportation of powder products. The hose is highly pliable and sustains high temperatures. The cover is weather and ozone resistant.

| Part no  | Bend radius (mm) | Working pressure (MPa) | ID (mm) | Vacuum pr. Max% | Length meter per coil | OD (mm) | Weight (kg) |
|----------|------------------|------------------------|---------|-----------------|-----------------------|---------|-------------|
| 15211032 | 175              | 1                      | 51      | 90              | 40                    | 63      | 1.7         |
| 15211048 | 270              | 1                      | 76      | 90              | 40                    | 90      | 2.74        |
| 15211064 | 400              | 1                      | 102     | 90              | 40                    | 116     | 4.12        |