

EXHAUST HOSE FOR HOT AIR, NEOPREN, SINGLE COATED



Product group	140
Cover design	Slightly corrugated
Color	Black
Bundled pipes/hoses	1
Media description	Ventilation
Antistatic wire	No
Cover tube material	CR
Flat coil	No
Max temperature (°C)	135
Reinforcement layers	1
Reinforcement materials	Steel spiral
Min temperature (°C)	-35

A hose suitable for transportation of hot steams, smoke and exhaust gases. Low-weight and very flexible, good in tight areas. The hose is non-inflammable and has good chemical resistance. Other dimensions are available on request.

Part no	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	Weight (kg)
15610016	17	0.15	25	5	4	0.12
15610020	19	0.15	32	5	4	0.16
15610029	26	0.15	44	4	4	0.21
15610032	30	0.15	51	4	4	0.25
15610040	36	0.13	63	4	4	0.31
15610048	42	0.11	76	3	4	0.42
15610055	49	0.11	89	3	4	0.5
15610064	55	0.11	102	2	4	0.56
15610080	69	0.09	127	2	4	0.8
15610096	81	0.08	152	1	4	1.04
15610180	94	0.06	180	1	4	1.21
15610203	107	0.06	203	1	4	1.39
15610254	132	0.04	254	0.5	4	2
15610305	158	0.01	305	0.3	4	2.41

