

Exhaust hose for hot air, Neoprene, double coated



Product group	140
Color	Black
Cover design	Slightly corrugated
Media description	Ventilation
Bundled pipes/hoses	1
Antistatic wire	No
Cover tube material	CR
Flat coil	No
Inner tube material	CR
Max temperature (°C)	135
Reinforcement layers	1
Reinforcement materials	Steel spiral
Min temperature (°C)	-35

A hose suitable for transportation of hot steams, smoke and exhaust gases. Low-weight and extremely flexible, good in tight areas. The hose is non-flammable and has good chemical resistance. Other dimensions are available on request.

Part no	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	Weight (kg)
15611016	14	0.28	25	70	4	0.15
15611020	20	0.27	32	60	4	0.17
15611029	27	0.26	44	50	4	0.26
15611032	31	0.26	51	50	4	0.29
15611040	37	0.24	63	50	4	0.36
15611048	43	0.21	76	40	4	0.46
15611055	50	0.2	89	40	4	0.53
15611064	56	0.19	102	30	4	0.6
15611080	70	0.14	127	30	4	0.86
15611096	82	0.12	152	20	4	1.1
15611180	95	0.1	180	10	4	1.28
15611203	108	0.07	203	10	4	1.43

