EXHAUST HOSE FOR HOT AIR, SILICONE, DOUBLE COATED



Product group	140
Color	Red
Cover design	Slightly corrugated
Media description	Ventilation
Bundled pipes/hoses	1
Flat coil	No
Inner tube material	Silicon
Antistatic wire	No
Cover tube material	Silicon
Max temperature (°C)	300
Reinforcement layers	1
Reinforcement materials	Steel spiral
Min temperature (°C)	-50

A hose suitable for transportation of hot steams, smoke and exhaust gases. Low-weight and extremely flexible, good in tight areas. The hose is non-inflammable and has good chemical resistance. Other dimensions are available on request.

Part no	ID (mm)	Vacuum pr. Max%	Length meter per coil	Bend radius (mm)	Working pressure (MPa)	Weight (kg)
15621016	25	7	4	18	0.28	1
15621020	32	6	4	20	0.26	0.17
15621029	44	5	4	27	0.26	1
15621032	51	5	4	31	0.26	0.29
15621040	63	5	4	37	0.24	0.36
15621048	76	4	4	43	0.21	0.46
15621055	89	4	4	50	0.2	0.53
15621064	102	3	4	56	0.19	0.6
15621080	127	3	4	70	0.14	0.86
15621096	152	2	4	82	0.12	1.1
15621180	180	1	4	95	0.1	1.28
15621203	203	1	4	108	0.07	1.43



HYDROSCAND