

Polyurethane hose M 0.7



Product group	140
Cover design	Corrugated
Bundled pipes/hoses	1
Media description	Materials
Cover tube material	PUR
Flat coil	No
Inner tube material	PUR
Antistatic wire	No
Max temperature (°C)	90
Reinforcement layers	No extra reinforcement
Reinforcement materials	Steel wire
Min temperature (°C)	-40

Powerful and flexible suction hose for transportation of materials such as gravels, cement, sand, sawdust, gasoline, oil products and grains. The hose is suitable in areas such as sawmills, plastic and paper industries, wood shaving, contractor businesses. Good resistant towards solvents and good aging characteristics. It is also resistant to oil mist and microbes.

Part no	Weight (kg/m)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	OD (mm)	Bend radius (mm)	Weight (kg)
15633012	0.17	0.14	20	40	15	25	20	-
15633016	-	0.33	25	80	10	30	30	0.25
15633020	-	0.25	32	71	10	40	40	0.35
15633024	-	0.21	38	66	10	46	46	0.39
15633025	-	0.21	40	66	10	48	48	0.4
15633032	-	0.17	51	52	10	58	58	0.45
15633038	-	0.15	55	44	10	63	63	0.51
15633040	-	0.13	63	37	10	71	72	0.48
15633041	-	0.13	65	37	10	73	73	0.65
15633044	-	0.11	70	37	10	78	78	0.68
15633048	-	0.11	76	29	10	84	84	0.6
15633050	-	0.1	80	29	10	88	88	0.65
15633055	-	0.08	90	22	10	99	99	0.73
15633064	-	0.08	102	22	10	110	110	0.84
15633070	-	0.07	110	22	10	119	119	1.03
15633074	-	0.07	115	22	10	124	124	1.15
15633076	-	0.07	120	22	10	129	129	1.16



Part no	Weight (kg/m)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	OD (mm)	Bend radius (mm)	Weight (kg)
15633080	-	0.07	127	22	10	135	135	1.18
15633096	-	0.06	152	15	10	161	161	1.48
15633140	-	0.06	140	15	10	149	149	1.38
15633160	-	0.06	160	15	10	170	170	1.74
15633165	-	0.04	165	15	10	175	175	1.78
15633170	-	0.04	170	15	10	180	180	1.8
15633175	-	0.04	175	15	10	185	185	1.85
15633180	-	0.04	180	15	10	190	190	1.9
15633203	-	0.04	203	15	10	214	214	2.3
15633220	-	0.03	220	7	10	230	230	2.52
15633228	-	0.03	228	7	10	238	240	2.63
15633254	-	0.03	254	7	10	264	264	3.02
15633305	-	0.03	305	7	10	315	315	3.22
15633318	-	0.03	318	7	10	328	330	3.38
15633350	-	0.01	350	7	10	360	360	3.6
15633400	-	0.01	400	5	10	410	410	4.45
15633450	-	0.01	450	5	10	460	460	5.06
15633500	-	0.01	500	5	10	510	510	5.7