Polyurethane hose HD T 2.0



Product group	140
Cover design	Corrugated
Bundled pipes/hoses	1
Media description	Materials
Antistatic wire	No
Cover tube material	PUR
Flat coil	No
Inner tube material	PUR
Max temperature (°C)	90
Reinforcement layers	No extra reinforcement
Reinforcement materials	Steel wire
Min temperature (°C)	-40

An extremely powerful PU-hose for both suction and pressure transports of abrasive materials such as sand, granulates and splinters. The hose is suitable in the contractor business area, the wood and plastic industries.

Part no	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	OD (mm)	Weight (kg)
15637025	100	0.43	40	94	10	50	0.76
15637032	125	0.4	51	94	10	61	1
15637038	140	0.38	55	89	10	65	1.1
15637039	150	0.36	60	89	10	70	1.32
15637048	190	0.29	76	89	10	87	1.51
15637056	225	0.24	90	89	10	103	1.81
15637064	250	0.21	102	87	10	115	2.13
15637070	275	0.2	110	87	10	124	2.82
15637096	450	0.15	152	82	10	167	4.08
15637160	500	0.14	160	81	10	175	4.81
15637170	600	0.12	170	80	10	185	5.1
15637200	800	0.1	200	0.85	10	217	6.43
15637203	950	0.11	203	66	10	220	6.43
15637250	1,300	0.09	250	51	10	267	7.91
15637300	1,600	0.06	300	42	10	317	9.45



HYDROSCAND