CORRUGATED SUCTION AND PRESSURE HOSE FOR AGRICULTURE



Product group	140
Cover design	Corrugated
Color	Black
Bundled pipes/hoses	1
Media description	Materials, Water
Safety factor	1:3
Cover tube material	SBR
Flat coil	No
Antistatic wire	No
Max temperature (°C)	80
Reinforcement layers	No extra reinforcement
Reinforcement materials	Steel wire, Textile
Min temperature (°C)	-30

Part no	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	OD (mm)	Bend radius (mm)	Weight (kg)
14657050	0.6	80	90	40	92	480	2.3
14657132	0.6	51	90	6	62	306	1.5
14657148	0.6	76	90	6	88	456	2.15
14657150	0.6	80	90	5	92	480	2.3
14657164	0.6	102	90	5	116	612	1
14657180	0.6	127	80	6	141	762	1
14657196	0.6	152	80	6	168	912	6.3
146571964	0.6	152	80	4	168	912	6.3
146572033	0.6	203	80	3	221	1,218	10
146572034	0.6	203	80	4	221	1,218	10
146572035	0.6	203	80	5	221	1,218	10
146572036	0.6	203	80	6	221	1,218	10
14657254	0.6	254	80	4	278	1,524	18
14657255	0.6	254	80	5	278	1,524	5
14657332	0.6	51	90	3	62	306	1.5
14657348	0.6	76	90	3	88	456	2.15
14657369	0.6	110	90	2.65	124	660	3.7
14657432	0.6	51	90	4	62	306	1.5



HYDROSCAND

Part no	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	OD (mm)	Bend radius (mm)	Weight (kg)
14657448	0.6	76	90	4	88	456	2.15
14657469	0.6	110	90	4	124	660	3.7
14657480	0.6	127	80	4	141	762	4.5
14657569	0.6	110	80	3	124	660	3.7
14657580	0.6	127	80	5	141	762	4.5

