

# Cyklone hose M53



|                                |                     |
|--------------------------------|---------------------|
| <b>Product group</b>           | 140                 |
| <b>Cover design</b>            | Corrugated          |
| <b>Color</b>                   | Black               |
| <b>Cover tube resistance</b>   | Abrasion, Weather   |
| <b>Inner tube resistance</b>   | Abrasion            |
| <b>Media description</b>       | Materials           |
| <b>Bundled pipes/hoses</b>     | 1                   |
| <b>Cover tube material</b>     | SBR                 |
| <b>Flat coil</b>               | No                  |
| <b>Inner tube material</b>     | NR                  |
| <b>Antistatic wire</b>         | No                  |
| <b>Max temperature (°C)</b>    | 90                  |
| <b>Reinforcement layers</b>    | 1                   |
| <b>Reinforcement materials</b> | Steel wire, Textile |
| <b>Min temperature (°C)</b>    | -30                 |

Flexible cyclone hose for mobile dry vacuum specially designed for mounting on top of the vacuum unit. Supplied in 2,6 meter with one spiral free end, and 3,2 meter lengths with two spiral free ends.

| Part no    | ID (mm) | Vacuum pr. Max% | Length meter per coil | OD (mm) | Bend radius (mm) | Weight (kg) |
|------------|---------|-----------------|-----------------------|---------|------------------|-------------|
| 14675304   | 204     | 90              | 2.6                   | 230     | 850              | 14          |
| 1467530490 | 204     | 90              | 3.2                   | 230     | 850              | 14          |

