SIGMA FS3310 - 40 SHORE



Product group	140
Cover design	Corrugated
Safety factor	1:3.2
Bundled pipes/hoses	1
Cover tube resistance	Oil, Water, Weather
Inner tube resistance	Antistatic
Media description	Materials
Antistatic wire	Yes
Cover tube material	CR
Flat coil	No
Max temperature (°C)	70
Reinforcement layers	1
Reinforcement materials	Steel wire, Textile
Min temperature (°C)	-35

A suction and delivery hose for the hydraulic transport of abrasive materials, such as gypsum, ashes, bauxite, corundum, dolomite, ores, feldspar, waste glass, wood chips, industrial waste, coal, metallic powder, etc.

Part no	Bend radius (mm)	Working pressure (MPa)	Vacuum pr. Max%	ID (mm)	Length meter per coil	OD (mm)	Weight (kg)
156790203	1,750	10	90	203	12	241	18
156790254	2,000	10	90	254	12	292	22
156790305	2,500	10	90	305	12	348	28
15679032	300	10	90	51	40	75	3
15679048	350	10	90	82	40	115	3.8
15679064	500	10	90	102	40	133	8
15679080	650	10	90	127	20	161	12
15679096	750	10	90	152	20	182	14



HYDROSCAND