

Straight fitting with male thread for pneumatics



Product group	519
Material	Aluminium
Shape	Straight
Max working pressure (Bar)	16
Manufacturer	Prevost
Measure A (mm)	32
Measure B (mm)	52
Max temperature (°C)	80
Min temperature (°C)	-20

Part no	OD (mm)	Thread type	Weight (g)	Thread	Dim C (mm)	Weight (kg)
54501141606	16	R	-	R 3/8" Male	26	0.05
54501141608	16	R	-	R 1/2" Male	26	0.05
54501142008	20	R	-	R 1/2" Male	32	0.07
54501142012	20	R	-	R 3/4" Male	32	0.08
54501142508	25	R	135	R 1/2" Male	38	0.14
54501142512	25	R	122	R 3/4" Male	32	0.12
54501142516	25	R	144	R 1" Male	38	0.14
54501143216	32	R	210	R 1" Male	46	0.21
54501143220	32	R	221	R 1 1/4" Male	46	0.22
54501144020	40	R	361	R 1 1/4" Male	57	0.36
54501144024	40	R	357	R 1 1/2" Male	57	0.36
54501145024	50	R	575	R 1 1/2" Male	72	0.58
54501145032	50	R	590	R 2" Male	72	0.59
54501146332	63	R	1,000	R 2" Male	90	1
54501146340	63	R	1,075	R 2 1/2" Male	90	1.08
54501148040	80	R	1,700	R 2 1/2" Male	110	1.7
54501148048	80	R	1,550	R 3" Male	110	1.55