

Straight fitting with male thread for pneumatics



Product group	519
Material	Aluminium
Shape	Straight
Max working pressure (Bar)	16
Manufacturer	Prevost
Measure A (mm)	32
Measure B (mm)	53
Max temperature (°C)	80
Min temperature (°C)	-20

Part no	Thread type	Thread	Dim C (mm)	OD (mm)	Weight (kg)
54501151606	G	G 3/8" Female	26	16	0.05
54501151608	G	G 1/2" Female	26	16	0.05
54501152008	G	G 1/2" Female	32	20	0.07
54501152012	G	G 3/4" Female	32	20	0.07
54501152508	G	G 1/2" Female	38	25	0.13
54501152512	G	G 3/4" Female	38	25	0.12
54501152516	G	G 1" Female	38	25	0.12
54501153216	G	G 1" Female	46	32	0.21
54501153220	G	G 1 1/4" Female	46	32	0.18
54501154020	G	G 1 1/4" Female	57	40	0.34
54501154024	G	G 1 1/2" Female	57	40	0.34
54501155024	G	G 1 1/2" Female	72	50	0.56
54501155032	G	G 2" Female	72	50	0.53
54501156332	G	G 2" Female	90	63	0.98
54501156340	G	G 2 1/2" Female	90	63	0.93
54501158040	G	G 2 1/2" Female	110	80	1.53
54501158048	G	G 3" Female	110	80	1.45