

Kappaflex 2K CO



Product group	100
Cover tube resistance	Abrasion, Oil, Weather
Inner tube resistance	Oil
Safety factor	1:4
Certificate	Det Norske Veritas
Max temperature (°C)	100
Reinforcement layers	2
Reinforcement materials	Steel wire
Min temperature (°C)	-40

Ozone resistant hose for applications with high pressures, well suited for marine applications. Exceeds EN 857 2SC. DNV-, MED- and MSHA-approved. Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/bobbin and a minimum length of 5 meters.

Part no	Working pressure (MPa)	Bend radius (mm)	ID (inch)	ID (mm)	OD (mm)	Weight (kg)
11051004	45	45	1/4"	6.5	13.4	0.28
1105100430	45	45	1/4"	6.5	13.4	0.28
11051005	42	60	5/16"	8	15	0.34
1105100530	42	60	5/16"	8	15	0.31
11051006	38.5	70	3/8"	10	17.4	0.39
1105100630	38.5	70	3/8"	10	17	0.39
11051008	34.5	90	1/2"	13	20.6	0.54
1105100830	34.5	90	1/2"	13	20.7	0.54
11051010	29	130	5/8"	16	23.7	0.66
11051012	28	160	3/4"	19	27.7	0.88
11051016	20	210	1"	25	35.6	1.18

