

# AQUASEWER, FLUSHING HOSE THERMOPLAST, 250 BAR



|                                |        |
|--------------------------------|--------|
| <b>Product group</b>           | 140    |
| <b>Cover design</b>            | Smooth |
| <b>Color</b>                   | Red    |
| <b>Media description</b>       | Water  |
| <b>Safety factor</b>           | 1:2.5  |
| <b>Bundled pipes/hoses</b>     | 1      |
| <b>Cover tube material</b>     | PU     |
| <b>Flat coil</b>               | No     |
| <b>Inner tube material</b>     | PE     |
| <b>Antistatic wire</b>         | No     |
| <b>Max temperature (°C)</b>    | 60     |
| <b>Reinforcement layers</b>    | 2      |
| <b>Reinforcement materials</b> | Nylon  |
| <b>Min temperature (°C)</b>    | -40    |

A hose suitable for high pressure sewage systems. The hose has low weight compared to rubber hoses, which leads to less abrasion and increased flowing speed. The hose sustains 3–4 times more external abrasion compared to a traditional rubber hose. It is delivered pre-assembled with fittings according to demand. Delivered with Pressure Test Certificate.

| Part no  | Working pressure (MPa) | ID (mm) | Length meter per coil | OD (mm) | Bend radius (mm) | Weight (kg) |
|----------|------------------------|---------|-----------------------|---------|------------------|-------------|
| 14190608 | 25                     | 13      | 60                    | 22.8    | 75               | 0.29        |
| 14190612 | 25                     | 19.6    | 60                    | 30.3    | 120              | 0.49        |
| 14190616 | 25                     | 25.9    | 60                    | 37.9    | 155              | 0.62        |
| 14190808 | 25                     | 13      | 80                    | 22.8    | 75               | 0.29        |
| 14190812 | 25                     | 19.6    | 80                    | 30.3    | 120              | 0.49        |
| 14190816 | 25                     | 25.9    | 80                    | 37.9    | 155              | 0.62        |
| 14191208 | 25                     | 13      | 120                   | 22.8    | 75               | 0.29        |
| 14191212 | 25                     | 19.6    | 120                   | 30.3    | 120              | 0.49        |
| 14191216 | 25                     | 25.9    | 120                   | 37.9    | 155              | 0.62        |
| 14191220 | 25                     | 32.4    | 120                   | 45.3    | 240              | 0.74        |
| 14191512 | 25                     | 19.6    | 150                   | 30.3    | 120              | 0.49        |
| 14191516 | 25                     | 25.9    | 150                   | 37.9    | 155              | 0.58        |
| 14191520 | 25                     | 32.4    | 150                   | 45.3    | 240              | 0.74        |

