

PU-Extra flex, Grey



Product group	518
Color	Grey
Safety factor	1:3
Antistatic wire	No
Flat coil	No
Max temperature (°C)	60
Min temperature (°C)	-40

Part no	Bend radius (mm)	Weight (kg/m)	Working pressure (MPa)	ID (mm)	Length meter per coil	OD (mm)
1937000302BW100	10	0.01	1.7	1.5	100	3
1937000302BW25	10	0.01	1.7	1.5	25	3
1937000302BW50	10	0.01	1.7	1.5	50	3
1937000403BW100	15	0.01	1.2	2.5	100	4
1937000403BW25	15	0.01	1.2	2.5	25	4
1937000604BW100	25	0.02	1.1	4	100	6
1937000604BW25	25	0.02	1.1	6	25	4
1937000806BW100	29	0.03	0.8	5.7	100	8
1937000806BW25	29	0.03	0.8	8	25	5.7
1937001007BW25	40	0.05	0.8	7	25	10
1937001007BW50	50	0.05	0.9	7	50	10
1937001208BW25	50	0.07	1	8	25	12
1937001208BW50	50	0.07	1	8	50	12
1937001410BW25	70	0.07	0.8	10	25	14
1937001410BW50	70	0.07	0.8	10	50	14

