

PU EXTRAFLEX, Transparent



Product group	518
Safety factor	1:3
Antistatic wire	No
Cover tube material	Polyurethane
Flat coil	No
Max temperature (°C)	80
Min temperature (°C)	-40

Part no	Bend radius (mm)	Weight (kg/m)	Working pressure (MPa)	ID (mm)	Length meter per coil	OD (mm)
1937000302C100	10	0.01	1.7	1.5	100	3
1937000302C25	10	0.01	1.7	1.5	25	3
1937000302C50	10	0.01	1.7	1.5	50	3
1937000403C100	15	0.01	1.2	2.5	100	4
1937000403C25	15	0.01	1.2	2.5	25	4
1937000604C100	25	0.02	1.1	4	100	6
1937000604C25	25	0.02	1.1	4	25	6
1937000806C100	29	0.03	0.8	5.7	100	8
1937000806C25	29	0.03	0.8	5.7	25	8
1937001007C25	40	0.05	8	7	25	10
1937001007C50	50	0.05	0.9	7	50	10
1937001208C100	50	0.07	1	8	100	12
1937001208C25	50	0.07	1	8	25	12
1937001208C50	50	0.07	1	8	50	12
1937001410C25	70	0.07	2.5	10	25	14
1937001410C50	70	0.07	0.8	10	50	14
1937001610C100	60	0.14	1.2	10	100	16

