

PU-Extraflex, blue



Product group	518
Color	Blue
Safety factor	1:3
Antistatic wire	No
Flat coil	No
Max temperature (°C)	60
Reinforcement layers	2
Min temperature (°C)	-40

Part no	OD (mm)	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Length meter per coil	Weight (kg)
1937000302Z25	3	10	1.7	1.5	25	0.01
1937000302Z50	3	10	1.7	1.5	50	0.01
1937000403Z100	4	15	1.2	2.5	100	0.01
1937000403Z25	4	15	1.2	2.5	25	0.01
1937000503Z25	5	20	1.3	3	25	0.02
1937000604Z100	6	25	1.1	4	100	0.02
1937000604Z25	6	25	1.1	4	25	0.02
1937000806Z100	8	29	0.8	5.7	100	0.03
1937000806Z25	8	29	0.8	5.7	25	0.03
1937001007Z25	8	29	0.8	5.7	25	0.03
1937001007Z50	10	50	0.9	7	50	0.05
1937001007Z500	10	50	0.9	7	500	0.05
1937001208Z25	12	50	1	8	25	0.07
1937001208Z50	12	50	1	8	50	0.07
1937001410Z25	14	70	0.8	10	25	0.07
1937001410Z50	14	70	0.8	10	50	0.07

