

Male Connector Sprint®



Product info	PTFE seal
Product group	518
Material	Nickel-plated brass
Manufacturer	Camozzi
Shape	Straight
Series	6 000
Max temperature (°C)	-20
Min temperature (°C)	80

Male Connector Sprint®

Part no	C	D	F	G	H	L	SW	SW1	Weight (g)	A
CS65101012	4.8	G1/2	16	24.5	9	25	22	8	39	10
CS65101014	8.3	G1/4	15.4	18.5	7	28.5	17	7	23	10
CS65101038	5.3	G3/8	15.4	20.5	8	25.5	19	8	27	10
CS65101212	5.8	G1/2	18.3	24.5	9	25	22	10	36	12
CS65101214	10.3	G1/4	18.3	20.5	7	29.5	19	7	26	12
CS65101238	9.3	G3/8	18.3	20.5	8	28.5	19	9	30	12
CS65101412	6.3	G1/2	20.5	24.5	9	26.5	22	12	34	14
CS65101438	10.3	G3/8	20.5	24.5	8	30.5	22	9	42	14
CS65101612	9	G1/2	23.5	26.5	9	32	24	-	42	16
CS65101634	3.5	G3/4	23.5	27.3	9	26.5	24	-	46	16
CS6510414	5.5	G1/4	8.8	15.2	7	19.5	14	2.5	15	4
CS6510418	3.8	G1/8	8.8	13.2	5.5	18	12	2.5	9	4
CS6510514	5.5	G1/4	9.8	15.2	7	20	14	3	14	5
CS6510518	3.8	G1/8	9.8	13.2	5.5	19	12	3	8	5
CS6510614	5.5	G1/4	11.7	15.2	7	21	14	4	14	6
CS6510618	6	G1/8	11.7	13.2	5.5	22	12	4	10	6
CS6510638	6.5	G3/8	11.7	20.5	8	22.5	19	4	27	6
CS6510812	7.5	G1/2	13.7	24.5	9	25	22	6	43	8
CS6510814	6.5	G1/4	13.7	15.2	7	24	14	6	14	8
CS6510818	7.5	G1/8	13.7	15.2	5.5	25	14	5	13	8
CS6510838	6	G3/8	13.7	20.5	8	23.5	19	6	25	8

Part no	C	D	F	G	H	L	SW	SW1	Weight (g)	A
---------	---	---	---	---	---	---	----	-----	------------	---

