

Elbow fitting, male thread



Product group	519
Material	Brass
Shape	90°
Max working pressure (Bar)	16
Manufacturer	Camozzi
Series	9 000
Max temperature (°C)	100
Min temperature (°C)	-50

Elbow fitting, male thread

Part no	SW1	Weight (g)	A	C	D	E	F	G	H	M	SW
C950210M12X15R7		47	10x1	8.2	M12X1.5	27	18.5	19	9	27	13
C950210M16X15R22		54	10x1	8.2	M16X1.5	27.5	18.5	24	9	27	13
C950210M22X15R7		68	10x1	8.2	M22X1.5	29	18.5	30	9	27	13
C950212M12X15R7		55.5	12x1.5	8.2	M12X1.5	28.5	20.5	19	9	28.5	15
C950212M16X15R22		59.5	12x1.5	8.2	M16X1.5	28.5	20.5	24	9	28.5	15
C950212M22X15R7		72.5	12x1.5	8.2	M22X1.5	30	20.5	30	9	28.5	15
C950215M16X15R22		91	15x1.5	8.2	M16X1.5	31.5	24.5	24	9	34	18
C950215M22X15R7		103	15x1.5	8.2	M22X1.5	34	24.5	30	9	34	18
C950216M22X15R7		117.5	16x1.5	8.2	M22X1.5	33	25	30	9	35.5	21
C950218M22X15R7		115	18x2	8.2	M22X1.5	33	27.5	30	9	35.5	21
C95026M10X1R 14		25	6x1	6	M10X1	22	14.5	16	7	22.5	9
C95026M12X15R 17		34	6x1	8.2	M12X1.5	25	14.5	19	9	22.5	9
C95026M16X15R 22		46.5	6x1	8.2	M16X1.5	26	14.5	24	9	23	11
C95028M10X1R 14		30.5	8x1	6	M10X1	23	16.5	16	7	25	11
C95028M12X15R 17		39.5	8x1	8.2	M12X1.5	26	16.5	19	9	25	11
C95028M14X15R 19		40	8x1	8.2	M14X1.5	26	16.5	21	9	25	11
C95028M16X15R 22		45.5	8x1	8.2	M16X1.5	26	16.5	24	9	25	11
C95028M22X15R 27		60	8x1	8.2	M22X1.5	29	16.5	30	9	25	11