

# 1456-10 ANACONDA, 25/30 BAR



<b>Product group</b>	140
<b>Color</b>	Yellow
<b>Cover design</b>	Smooth
<b>Safety factor</b>	1:3
<b>Bundled pipes/hoses</b>	1
<b>Cover tube resistance</b>	Heat, Ozone
<b>Inner tube resistance</b>	Heat
<b>Media description</b>	Chemicals, Water, Air
<b>Antistatic wire</b>	No
<b>Cover tube material</b>	EPDM
<b>Flat coil</b>	No
<b>Inner tube material</b>	EPDM
<b>Max temperature (°C)</b>	100
<b>Reinforcement layers</b>	2
<b>Reinforcement materials</b>	Textile
<b>Min temperature (°C)</b>	-40

A very flexible hose with a wide temperature range. Well suited for air and hot and cold water. It is resistant towards lighter chemicals. It has good ozone resistance. 6-38mm have a smooth cover and 42-65mm have a wrapped cover. Electrically conductive tube construction prevents the build-up of static electricity.  $R < 10^6$  AdBlue resistant. Temperature range -40°C / +120°C ; max. +100°C fluid temperature in closed systems.

Part no	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Length meter per coil	OD (mm)	Weight (kg)
14561004	40	3	6	40	14	0.18
14561005	50	3	8	40	17	0.26
14561006	60	3	10	40	20	0.34
14561008	80	3	13	40	23	0.41
14561010	100	3	16	40	27	0.55
14561012	115	3	19	40	30	0.63
14561016	150	2.5	25	40	37	0.87
14561020	200	2.5	32	40	44	1.14
14561024	250	2.5	38	40	51	1.4
14561026	340	2.5	42	40	56	1.56
14561032	400	2.5	50	40	66	2.03
14561040	520	2.5	65	40	83	2.71

