

T-koppling Hane, Svivlande Sprint®



Produktinfo

Produktgrupp

Material

Tillverkare

Form

Maxtemperatur (°C)

Mintemperatur (°C)

Med nylontätning PTFE

518

Nickelpläterad mässing

Camozzi

T

-20

80

Artikelnummer	SW	SW1	A	C	D	E	F	H	L
CS64301012	13	22	10	5.8	G1/2	19.5	16.5	9	52
CS64301014	13	14	10	5.8	G1/4	18.5	16.5	7	52
CS64301038	13	19	10	5.8	G3/8	19	16.5	8	52
CS64301212	15	22	12	7.3	G1/2	20.5	19.5	9	53
CS64301214	15	17	12	7.3	G1/4	20	19.5	7	53
CS64301238	15	19	12	7.3	G3/8	20	19.5	8	53
CS64301412	17	22	14	8.3	G1/2	21.5	21.5	9	57
CS6430418	8	12	4	3.5	G1/8	14.5	9	5.5	35
CS6430514	9	14	5	5.5	G1/4	14.5	10	7	41
CS6430518	9	12	5	5.5	G1/8	14.5	10	5.5	41
CS6430614	9	14	6	4	G1/4	15	12.7	7	40
CS6430618	9	12	6	4	G1/8	15	12.7	5.5	40
CS6430814	11	14	8	5	G1/4	16	14.2	7	45
CS6430818	11	12	8	5	G1/8	16	14.2	5.5	45
CS6430838	11	19	8	5	G3/8	16.5	14.2	8	45