

Stående T-koppling, Svivlande Sprint®



Produktinfo

Produktgrupp

Material

Form

Tillverkare

Maxtemperatur (°C)

Mintemperatur (°C)

Med nylontätning PTFE

518

Nickelpläterad mässing

T

Camozzi

-20

80

Artikelnummer	SW	SW1	A	C	D	E	F	H	L
CS64401014	13	14	10	5.8	G1/4	18.5	16.5	7	51.5
CS64401038	13	19	10	5.8	G3/8	18.5	16.5	8	53
CS64401238	15	19	12	7.3	G3/8	19.5	19.5	8	54.5
CS64401412	17	22	14	8.3	G1/2	21.5	21.5	9	59
CS6440418	8	12	4	3.5	G1/8	14.5	9	5.5	37.5
CS6440518	9	12	5	5.5	G1/8	14.5	10	5.5	40.5
CS6440614	9	14	6	4	G1/4	15	12.7	7	42
CS6440618	9	12	6	4	G1/8	15	12.7	5.5	40.5
CS6440814	11	14	8	5	G1/4	16	14.2	7	45.5
CS6440818	11	12	8	5	G1/8	16	14.2	5.5	44
CS6440838	11	19	8	5	G3/8	16.5	14.2	8	47